

# Flexible, reliable and user friendly.

The TM8110 and TM8115 are robust, software-flexible radios which are ideal for a wide range of voice and data applications. The TM8110 comes with 10 conventional channels and one-digit display. The TM8115 comes with 100 conventional channels and two-digit display.



## KEY FEATURES

- ▶ Easy-to-read display for fast channel selection
- ▶ Four programmable function keys
- ▶ Heavy duty microphone and built-in loudspeaker
- ▶ Data capable - supports 1200/2400 baud FFSK as standard
- ▶ Internal high speed data modem (12 kbps on NB channels/19.2 kbps on WB channels) (software option)
- ▶ Type 99 (2-tone) decode
- ▶ Four RF power levels
- ▶ Full Selcall functionality
- ▶ DTMF encoder
- ▶ Low standby power consumption
- ▶ MDC 1200 encode (software option)
- ▶ Multiple auxiliary ports
- ▶ Expansive internal options area
- ▶ Direct connect GPS



#### **Engineered to be tough**

The TM8110 and TM8115 exceeds stringent reliability specifications, including MIL-STD 810 C, D, E, F and IP54.

#### **Software feature upgrades**

The Software Feature Enabler (SFE) allows system operators to upgrade with additional functionality at any stage by simply purchasing the appropriate software license key.

#### **Improved data integrity**

The application of Digital Signal Processor (DSP) technology optimizes RF performance and ensures fast and reliable data processing.

#### **Ease of integration**

The system integrator has maximum design flexibility with multiple ports for auxiliary connectors and a large options board area. The comprehensive third party developer's kit provides integrators with hardware and software tools to facilitate customization.

#### **AVL support**

The TM8110/TM8115 support a standard polling vehicle location format and a direct connect port for an external GPS receiver, allowing for the development of a complete AVL solution.

**GENERAL**

	<b>Band</b>	<b>Operational Frequency</b>		<b>Transmit Power</b>
VHF	A4	66–88MHz		25W
	B1	136–174MHz		25W
	B1	136–174MHz		50W
	D1	216–266MHz		25W
UHF	H5	400–470MHz		25W
	H5	400–470MHz		40W
	H6	450–530MHz		25W
	H7	450–520MHz		40W
700/800MHz	K5	<b>Transmit</b> 762–776MHz	<b>Receive</b> 762–776MHz	30W (<806MHz)
		792–825MHz		35W (>806MHz)
		850–870MHz	850–870MHz	
900MHz	L3	896–941MHz	935–941MHz	30W
Frequency Stability	±1.5ppm			
Channel/Network Capacity	TM8110: 10 Channels (simplex or semi-duplex) TM8115: 100 Channels (simplex or semi-duplex)			
Power Supply	10.8–16VDC			
Channel Spacing	12.5/20/25kHz			
Channel Increment	7.5/12.5/15/20/25/30kHz			
Dimensions (DxWxH)	6.9 x 6.3 x 2.0in (175 x 160 x 51mm)			
25W	7.7 x 6.3 x 2.0in (195 x 160 x 51mm)			
30/35/40/50W				
Weight	45.9oz (1.3kg)			
25W	53oz (1.5kg)			
30/35/40/50W				
Operational Temperature	-22°F to +140°F (-30°C to +60°C)			
Sealing	IP54			
RF Connector	50 ohm BNC or Mini UHF			
Interface Connecters	3 Interface Connecters with Serial Ports			
Internal Speaker Output	>3W			

**TRANSMITTER**

	<b>VHF/UHF (TIA/EIA)</b>	<b>700/800MHz (TIA/EIA)</b>
Output Power		
25W	25W, 12W, 5W, 1W	
30W		
35W		30W, 15W, 5W, 2W
40W UHF	40W, 20W, 15W, 10W	35W, 15W, 5W, 2W
50W VHF	50W, 25W, 15W, 10W	
Modulation Limiting		
12.5kHz	±2.5kHz	±2.5kHz
20kHz	±4kHz	±4kHz
25kHz	±5kHz	±5kHz
FM Hum and Noise		
12.5kHz	-38dB	-33dB
20kHz	-41dB	-38dB
25kHz	-43dB	-40dB
Conducted/Radiated Emissions	-36dBm < 1GHz -30dBm > 1GHz	<-30dBm to 8GHz
Audio Response Bandwidth	300Hz–3kHz	300Hz–3kHz
Audio Response	Flat or pre-emphasised	Flat or pre-emphasised
Audio Distortion	< 3% at 1kHz 60% deviation	< 3% at 1kHz 60% deviation
Transmit Rise Time	10ms	10ms
Duty Cycle		
25W	33%	
30/35W		20%
40/50W	20%	

**RECEIVER\*\***

	VHF/UHF (TIA/EIA)	700/800MHz (TIA/EIA)
Sensitivity	0.28µV (<-118dBm) for 12dB SINAD	0.22µV (-120dBm) for 12dB SINAD 0.35µV (<-116dBm) for 20dB SINAD
Intermodulation	75dB	82dB
Selectivity		
12.5kHz	65dB	67dB
20kHz	70dB	75dB
25kHz	75dB	79dB
Spurious Responses	75dB	> 90dB***
Hum and Noise		
12.5kHz	-40dB	-44dB
20kHz	-41dB	-47dB
25kHz	-43dB	-48dB
Audio Response Bandwidth	300Hz-3kHz	300Hz-3kHz
Audio Response	Flat or de-emphasized	Flat or de-emphasized
Audio Distortion	< 3% at 1kHz 60% deviation	< 3% at 1kHz 60% deviation

**MILITARY STANDARDS 810 F\***

Applicable MIL-STD	Method	Procedure
Low Pressure	500.4	2
High Temperature	501.4	1, 2
Low Temperature	502.4	1, 2
Temperature Shock	503.4	1
Solar Radiation	505.4	1
Rain	506.4	3
Humidity	507.4	1
Salt Fog	509.4	1
Dust	510.4	1
Vibration	514.5	1
Shock	516.5	1, 6

**REGULATORY DATA**

	Frequency	FCC Description	IC Description
25W	136-174	CASTMAB1A	737A-TMAB1A
	216-266	CASTMAD1A	
	400-470	CASTMAH5A	737A-TMAH5A
	450-530	CASTMAH6A	737A-TMAH6A
35W	806-869	CASTMAK5B	737A-TMAK5B
40W	400-470	CASTMAH5B	
	450-520	CASTMAH7B	
50W	136-174	CASTMAB1B	

Authorized Partners

Tait is your complete supplier of radio communications equipment offering mobile, portable and infrastructure solutions. Tait is renowned for its flexibility, responsiveness and commitment to producing innovative world-class mobile radio communications products.

Specifications are subject to change without notice and shall not form part of any contract. They are issued for guidance purposes only.

+Please note that not all frequency bands and power outputs are available in all markets. For further information please check with your nearest Tait office or authorized dealer.

The word "Tait" and the Tait logo are trademarks of Tait Limited. Tait is an ISO 9001:2008 and ISO 14001:2004 certified supplier.

